

Chassis TFT-LCD Touch Display



Features

- ❖ Equipped with 15", 17" or 19" high brightness TFT LCD Display
- ❖ Alternate Resistive and SAW touchscreens
- ❖ Front-panel controls for display settings
- ❖ VESA mount compatible

Specification

LCD Display >>>

CL-150	Size : 15" (4:3) Resolution : 1024 x 768 Brightness : 500cd/m ² Backlight : CCFL / LED Life Time : MTBF=50000 Hrs
CL-170	Size : 17" (4:3) Resolution : 1280 x 1024 Brightness : 300cd/m ² Backlight : CCFL / LED Life Time : MTBF=50000 Hrs
CL-190	Size : 19" (4:3) Resolution : 1280 x 1024 Brightness : 300cd/m ² Backlight : CCFL / LED Life Time : MTBF=50000 Hrs

Touch screen >>>

Options	5-wire Resistive Touchscreen, SAW Touchscreen, Abrasion-resistant tempered glass, Touchscreen protector optical film
---------	---

I/O Interface >>>

External I/O Port	(1) RS232 or (1) USB port for touch screen (1) VGA
-------------------	---

Power input >>>

DC-Jack	Screw-type
Power supply	External power adapter can be bolted to DC-Jack
Terminal block	Optional Phoenix terminal block

Mechanical >>>

Construction	Heavy-duty Steel- SPGC
Mounting	VESA mount (100x100) compatible
Dimension	CL-150 : 390(W) x 310(H) x 40(D)mm CL-170 : 450(W) x 360(H) x 65(D)mm CL-190 : 480(W) x 395(H) x 65(D)mm
Net Weight	CL-150 : 6.9 Kgs CL-170 : 7.7 Kgs CL-190 : 9.1 Kgs

Environmental >>>

Operating Temp.	0°C ~ 50°C
Storage Temp.	-20°C to 80°C
Relative Humidity	5% to 95%, non-condensed

EMC Compliance & Safety >>>

	CE/FCC
--	--------

Ordering Information

CL-150T	15" Chassis TFT-LCD Touch Display
CL-150	15" Chassis TFT-LCD Display
CL-170T	17" Chassis TFT-LCD Touch Display
CL-170	17" Chassis TFT-LCD Display
CL-190T	19" Chassis TFT-LCD Touch Display
CL-190	19" Chassis TFT-LCD Display