

Rackmount TFT-LCD Touch Display



Features

- ❖ Equipped with 15", 17" or 19" high brightness TFT LCD Display
- ❖ Alternate Resistive and SAW touchscreens
- ❖ Front-panel controls for display settings
- ❖ Rackmount and VESA mount compatible

Specification

LCD Display >>>

RL-150	Size : 15" (4:3) Resolution : 1024 x 768 Brightness : 500cd/m ² Backlight : CCFL / LED Life Time : MTBF=50000 Hrs
RL-170	Size : 17" (4:3) Resolution : 1280 x 1024 Brightness : 300cd/m ² Backlight : CCFL / LED Life Time : MTBF=50000 Hrs
RL-190	Size : 19" (4:3) Resolution : 1280 x 1024 Brightness : 300cd/m ² Backlight : CCFL / LED Life Time : MTBF=50000 Hrs

Touch screen >>>

Options	5-wire Resistive Touchscreen, SAW Touchscreen, Abrasion-resistant tempered glass, Touchscreen protector optical film
---------	---

I/O Interface >>>

External I/O Port	(1) RS232 or (1) USB port for touch screen (1) VGA
-------------------	---

Power input >>>

DC-Jack	Screw-type
Power supply	External power adapter can be bolted to DC-Jack
Terminal block	Optional Phoenix terminal block

Mechanical >>>

Construction	Heavy-duty Steel- SPGC
Mounting	Rackmount, and VESA mount (75x75) (100x100) compatible
Dimension	RL-150 : 438(W) x 266(H) x 38(D)mm RL-170 : 438(W) x 310(H) x 45(D)mm RL-190 : 438(W) x 350(H) x 48(D)mm
Net Weight	RL-150 : 6.9 Kgs RL-170 : 7.7 Kgs RL-190 : 9.1 Kgs

Environmental >>>

Operating Temp.	0°C ~ 50°C
Storage Temp.	-20°C to 80°C
Relative Humidity	5% to 95%, non-condensed

EMC Compliance & Safety >>>

	CE/FCC
--	--------

Ordering Information

RL-150T	15" Rackmount TFT-LCD Touch Display
RL-150	15" Rackmount TFT-LCD Display
RL-170T	17" Rackmount TFT-LCD Touch Display
RL-170	17" Rackmount TFT-LCD Display
RL-190T	19" Rackmount TFT-LCD Touch Display
RL-190	19" Rackmount TFT-LCD Display